



**WEATHERPROOF
Series**

"JOHNSON" - WEATHERPROOF series, Emergency Exit / Directional Sign box.
Maintained type. Made of GMS with white powder coating, assembled inside the case with IP65 weatherproof fluorescent batten, It's able to used for outdoor, pump room and high humidity areas.

"強生牌" 防水系列, 長明式緊急照明出口指示燈箱, 設計利用防水螢光支架 (IP65) 內藏於燈箱。
 適合戶外, 泵房及較潮濕範圍使用。

SPECIFICATION & TECHNICAL DATA

規格及技術資料

NI-CD RECHARGEABLE BATTERY

| MODEL 套件型號 | | JX8CN2 | JX20CN2 | JX14CN2 |
|---------------------------------------|-----|---------------|---------------|---------------|
| Internal W/P Fluo. fitting 內藏防水支架 | | JBA008F-N2F | JC20N2-WP | JC14N2-WP |
| Wattage 適用瓦數 | (W) | 8W | T8 / 18W | T5 /14W |
| Battery Capacity & Voltage 電池容量及電壓 | | 5 x 1.8AH, 6V | 5 x 1.8AH, 6V | 5 x 1.8AH, 6V |
| Emergency Output 緊急照明輸出流明 | | 100 lumens | 300 lumens | 250 lumens |
| Minimum Recharging Time 電池充滿所需時間 | (h) | 12 hours | | |

NI-CD RECHARGEABLE BATTERY

| MODEL 套件型號 | | JX8CN3 | JX20CN3 | JX14CN3 |
|---|--------|--|-----------------|-----------------|
| Internal W/P Fluo. fitting 內藏防水支架 | | JBA008F-N3F | JC20N3-WP | JC14N2-WP |
| Wattage 適用瓦數 | (W) | 8W | T8 / 18W | T5 /14W |
| Battery Capacity & Voltage 電池容量及電壓 | | 5 x 2.5AH, 6V | 5 x 2.5AH, 6V | 5 x 2.5AH, 6V |
| Emergency Output 緊急照明輸出流明 | | 100 lumens | 300 lumens | 250 lumens |
| Minimum Recharging Time 電池充滿所需時間 | (h) | 12 hours for 2 hours discharge, 24 hours for 3 hours discharge | | |
| Dimension of Metal casing 燈箱呎吋 (L x H x D) | (mm) | 450 x 200 x 150 | 700 x 200 x 150 | 700 x 250 x 150 |
| Signage Panel 燈箱膠片字樣及圖案 | | EXIT 出口 or Escape Route Sign | | |
| Main Voltage / Frequency 市電(交流電)輸入電壓 / 頻率 | (V) | A/C 220V (+ / - 10%) / 50Hz | | |
| Emergency Starting Time 套件緊急照明啟動時間 | (sec.) | < 0.3 | | |
| Operating Frequency 套件運作頻率 | (kHz) | 25~28 | | |
| Operating Temperature 套件運作環境溫度 | (ta) | 0°C - 55 °C | | |
| Charge Indicator 充電指示 | | Red LED | | |
| Test Button 測試掣 | | Press Type | | |
| Low Voltage Protection 低壓截止保護線路 | | Electronic Protection (approx. 1V / cell) | | |
| Compliance To 達致認可標準 | | BS 5266-1, BS EN 60598-2-22 and FSD PPA/104A(4th Revision) | | |
| Guarantee Period 保用期 | (M) | 12 months | | |

Options: Sealed Ni-MH High Temp. Rechargeable Battery will be available on request.

: Clients can choose stainless steel casing and 30% or 50% lumen output when mains fail.

: Weatherproof fluo. Batten can be provided by clients or by 'JOHNSON'.



JOHNSON



ISO9001:2008
Certificate No: FM56403



JX14HN2-WP, 1x14W Emergency EXIT sign box, weatherproof type, c/w NI-MH rechargeable battery.



1x14W weatherproof fluo. batten (IP65) is built in the sign box. It can be discharged for 2 or 3 hours.



A completed set sign box can be provided normal, 30% or 50% lumens output after main supply failure.



Hairline stainless steel casing is another sign box which contains IP65 W/P fluo. batten for outdoor use.

