



The Characteristic Sign Box in Macau Clip On T8 Series

"JOHNSON" - CLIP ON series, Emergency Exit / Directional Sign Box, Maintained type.
Application for popular and economical emergency luminaires. The plastic panel is clipped-on to the rigid housing by means for two screws.

"強生牌" 趟片式系列，長明式緊急照明出口指示燈箱，指示膠片直接趟入燈箱前部份，燈箱修邊鐵片，只需由兩粒螺絲固定。

SPECIFICATION & TECHNICAL DATA

規格及技術資料

NI-CD RECHARGEABLE BATTERY

| MODEL 套件型號 | | JX10CN2-Q | JX20CN2-Q |
|---------------------------------------|-----|---------------|---------------|
| Internal Conversion Kit 內藏電池套件 | | JF10N2 | JF20N2 |
| Wattage 適用瓦數 | (W) | T8 / 10W | T8 / 18W |
| Battery Capacity & Voltage 電池容量及電壓 | | 5 x 1.8AH, 6V | 5 x 1.8AH, 6V |
| Emergency Output 緊急照明輸出流明 | | 300 lumens | 350 lumens |
| Minimum Recharging Time 電池充滿所需時間 | (h) | 12 hours | |

NI-CD RECHARGEABLE BATTERY

| MODEL 套件型號 | | JX10CN3-Q | JX20CN3-Q |
|---|--------|--|----------------|
| Internal W/P Fluo. fitting 內藏電池套件 | | JF10N3 | JF20N3 |
| Wattage 適用瓦數 | (W) | T8 / 10W | T8 / 18W |
| Battery Capacity & Voltage 電池容量及電壓 | | 5 x 2.5AH, 6V | 5 x 2.5AH, 6V |
| Emergency Output 緊急照明輸出流明 | | 300 lumens | 350 lumens |
| Minimum Recharging Time 電池充滿所需時間 | (h) | 12 hours | |
| Dimension of Metal casing 燈箱呎吋 (L x H x D) | (mm) | 440 x 170 x 90 | 650 x 180 x 75 |
| Signage Panel 燈箱膠片字樣及圖案 | | 出SAIDA口, SAIDA出口 or Escape Route Sign | |
| Main Voltage / Frequency 市電(交流電)輸入電壓 / 頻率 | (V) | A/C 220V (+ / - 10%) / 50Hz | |
| Emergency Starting Time 套件緊急照明啟動時間 | (sec.) | < 0.3 | |
| Operating Frequency 套件運作頻率 | (kHz) | 25~28 | |
| Operating Temperature 套件運作環境溫度 | (ta) | 0°C - 55 °C | |
| Charge Indicator 充電指示 | | Red LED | |
| Test Button 測試掣 | | Press Type | |
| Low Voltage Protection 低壓截止保護線路 | | Electronic Protection (approx. 1V / cell) | |
| Compliance To 達致認可標準 | | BS 5266-1, BS EN 60598-2-22 and FSD PPA/104A(4th Revision) | |
| Guarantee Period 保用期 | (M) | 12 months | |

Options : Sealed Ni-MH High Temp. Rechargeable Battery will be available on request.

: Clients can choose 30% or 50% lumen output when mains fail.



JOHNSON



ISO9001:2008
Certificate No:FM56403

Self-contained emergency sign box can be complied with Macau FSD requirement. It is maintained type and can be surface and recessed type. The characters can be single and double sided.



JX10CNH3-T, 1x10W Emergency Sign box, white escape route with left directional arrow on green background.



JX10CN3-Q, 1x10W Emergency Sign box, white L/C on green background.

