

The Characteristic Sign Box in Macau Clip On T5 Series

"JOHNSON" - CLIP ON series, Emergency Exit / Directional Sign Box, Maintained type.

Application for popular and economical emergency luminaires. The plastic panel is clipped-on to the rigid housing by means for two screws.

"強生牌" 趙片式系列,長明式緊急照明出口指示燈箱,指示膠片直接趙入燈箱前部份, 燈箱修邊鐵片,只需由兩粒螺絲固定。

SPECIFICATION & TECHNICAL DATA

規格及技術資料

NI-CD RECHARGEABLE BATTERY

MODEL 套件型號		JX8CN2-Q	JX14CN2-Q		
Internal Conversion Kit 內藏電池套件		JF8N2	JF14N2		
Wattage 適用瓦數	(W)	T5 / 8W	T5 / 14W		
Battery Capacity & Voltage 電池容量及電壓		5 x 1.8AH, 6V	5 x 1.8AH, 6V		
Emergency Output 緊急照明輸出流明		300 lumens	350 lumens		
Minimum Recharging Time 電池充滿所需時間	(h)	12 hours			

NI-CD RECHARGEABLE BATTERY

MODEL 套件型號		JX8CN3-Q	JX14CN3-Q	
Internal W/P Fluo. fitting 內藏電池套件		JF8N3	JF14N3	
Wattage 適用瓦數	(W)	T5 / 8W	T5 / 14W	
Battery Capacity & Voltage 電池容量及電壓		5 x 2.5AH, 6V	5 x 2.5AH, 6V	
Emergency Output 緊急照明輸出流明		300 lumens	350 lumens	
Minimum Recharging Time 電池充滿所需時間	(h)	12 hours		
Dimension of Metal casing 燈箱呎吋 (LxHxD)	(mm)	440 x 170 x 90	650 x 180 x 75	
Signage Panel 燈箱膠片字樣及圖案		出SAIDA□, SAIDA出□ or Escape Route Sign		
Main Voltage / Frequency 市電(交流電)輸入電壓 / 頻率	(V)	A/C 220V (+ / - 10%) / 50Hz		
Emergency Starting Time 套件緊急照明啓動時間	(sec.)	< 0.3		
Operating Frequency 套件運作頻率	(kHz)	25~28		
Operating Temperature 套件運作環境溫度	(ta)	0℃ - 55 ℃		
Charge Indicator 充電指示		Red LED		
Test Button 測試掣		Press Type		
Low Voltage Protection 低壓截止保護線路		Electronic Protection (approx. 1V / cell)		
Compliance To 達致認可標準		BS 5266-1, BS EN 60598-2-22 and FSD PPA/104A(4th Revision)		
Guarantee Period 保用期	(M)	12 months		

Options : Sealed Ni-MH High Temp. Rechargeable Battery will be available on request.

[:] Clients can choose 30% or 50% lumen output when mains fail.



JOHNSON (ISO9001:2008 Certificate No.FM56403

Self-contained emergency sign box can be complied with Macau FSD requirement. It is maintained type and can be surface and recessed type. The characters can be single and double sided.



JX8CNH3-T, 1x8W Emergency Sign box, white escape route with left directional arrow on green background.



JX8CN3-Q, 1x8W Emergency Sign box, white L/C on green background.

