



The Characteristic Sign Plate in Macau Suspension T8 Series

"JOHNSON" - SUSPENSION series Emergency Sign Plate. Maintained type.
Application for practical and economical emergency luminaire,
suitable for surface / recessed mounted.

"強生牌" 懸掛式系列，長明式緊急照明指示吊牌，設計以經濟實用為原則，
適合明裝 / 暗藏天花安裝。

SPECIFICATION & TECHNICAL DATA

規格及技術資料

NI-CD RECHARGEABLE BATTERY

MODEL 套件型號		JXP10R / SN2-Q	JXP20R / SN2-Q
Internal Conversion Kit 內藏電池套件		JF10N2	JF20N2
Wattage 適用瓦數	(W)	T8 / 10W	T8 / 18W
Battery Capacity & Voltage 電池容量及電壓		5 x 1.8AH, 6V	5 x 1.8AH, 6V
Emergency Output 緊急照明輸出流明		300 lumens	350 lumens
Minimum Recharging Time 電池充滿所需時間	(h)	12 hours	

NI-CD RECHARGEABLE BATTERY

MODEL 套件型號		JXP10R / SN3-Q	JXP20R / SN3-Q
Internal W/P Fluo. fitting 內藏電池套件		JF10N3	JF20N3
Wattage 適用瓦數	(W)	T8 / 10 W	T8 / 18 W
Battery Capacity & Voltage 電池容量及電壓		5 x 2.5AH, 6V	5 x 2.5AH, 6V
Emergency Output 緊急照明輸出流明		300 lumens	350 lumens
Minimum Recharging Time 電池充滿所需時間	(h)	12 hours	
Dimension of Metal casing 吊牌箱呎吋 (L x H x D)	(mm)	440 x 120 x 70	670 x 120 x 70
Dimension of Perspex 水晶吊牌呎吋 (L x H x T)	(mm)	400 x 200 x 9	550 x 200 x 9
Signage Panel 燈箱膠片字樣及圖案		出SAIDA口, SAIDA出口 or Escape Route Sign	
Main Voltage / Frequency 市電(交流電)輸入電壓 / 頻率	(V)	A/C 220V (+ / - 10%) / 50Hz	
Emergency Starting Time 套件緊急照明啟動時間	(sec.)	< 0.3	
Operating Frequency 套件運作頻率	(kHz)	25~28	
Operating Temperature 套件運作環境溫度	(ta)	0°C - 55 °C	
Charge Indicator 充電指示		Red LED	
Test Button 測試掣		Press Type	
Low Voltage Protection 低壓截止保護線路		Electronic Protection (approx. 1V / cell)	
Compliance To 達致認可標準		BS 5266-1, BS EN 60598-2-22 and FSD PPA/104A(4th Revision)	
Guarantee Period 保用期	(M)	12 months	

Options : Sealed Ni-MH High Temp. Rechargeable Battery will be available on request.

: Clients can choose 30% or 50% lumen output when mains fail.

: R - Recessed mount; S - Surface mount



JOHNSON



ISO9001:2008
Certificate No:FM56403

Self-contained emergency sign plate is used in Macau projects. It can be surface and recessed mount with single and double sided. The characters are depended on the clients needs.



JXP10R/SN3-T , 1x10W Emergency Sign plate with white escape route sign with left directional arrow on green background.



JXP20R/SN3-Q, 1x18W Emergency Sign plate with white L/C in green background.



JXP10R/SN3-W

