®

The Characteristic Sign Plate in Macau ELITE T8 Series

"JOHNSON" - ELITE series Emergency Sign Plate which is installed inside the false ceiling. Designed for easy installation and maintainence. By apply a force, the Perspex attached to the bottom cover of the fitting is easily pull down from the body of the fixture,

"強生牌"精緻式系列, 長明式緊急照明出口指示吊牌,設計便利安裝及方便維修, 用力拉下,燈箱底冚同水晶吊牌就輕易地與暗藏天花燈箱分離,易於維修。

SPECIFICATION & TECHNICAL DATA

規格及技術資料

NI-CD RECHARGEABLE BATTERY

ZUITIZATA PRO RATI		1		
MODEL 套件型號		JXP10SN2-Elite-Q	JXP20 SN2-Elite-Q	
Internal Conversion Kit 內藏電池套件		JF10N2	JF20N2	
Wattage 適用瓦數	(W)	T8 / 10W	T8 / 18W	
Battery Capacity & Voltage 電池容量及電壓		5 x 1.8AH, 6V	5 x1.8AH, 6V	
Emergency Output 緊急照明輸出流明		300 lumens	350 lumens	
Minimum Recharging Time 電池充滿所需時間	(h)	12 hours		

NI-CD RECHARGEABLE BATTERY

MODEL 套件型號		JXP10SN3-Elite-Q	JXP20SN3-Elite-Q	
Internal W/P Fluo. fitting 內藏電池套件		JF10N3	JF20N3	
Wattage 適用瓦數	(W)	T8 /10 W	T8 / 18 W	
Battery Capacity & Voltage 電池容量及電壓		5 x 2.5AH, 6V	5 x 2.5AH, 6V	
Emergency Output 緊急照明輸出流明		300 lumens	350 lumens	
Minimum Recharging Time 電池充滿所需時間	(h)	12 hours for 2 hours discharge, 24 hours for 3 hours discharge		
Dimension of Metal casing 吊牌箱呎吋 (L1 x H1 x D)	(mm)	440 x 100 x 100	670 x 100 x 100	
Dimension of Bottom Plate 底部鐵片呎吋 (L2 x W)	(mm)	480 x 120	720 x 150	
Dimension of Perspex 水晶吊牌呎吋 (L3 x H2 x T)	(mm)	400 x 180 x 9	550 x 180 x 9	
Signage Panel 燈箱膠片字樣及圖案		出SAIDA口, SAIDA出口 or Escape Route Sign		
Main Voltage / Frequency 市電(交流電)輸入電壓 / 頻率	(V)	A/C 220V (+ / - 10%) / 50Hz		
Emergency Starting Time 套件緊急照明啓動時間	(sec.)	< 0.3		
Operating Frequency 套件運作頻率	(kHz)	25~28		
Operating Temperature 套件運作環境溫度	(ta)	0℃ - 55 ℃		
Charge Indicator 充電指示		Red LED		
Test Button 測試掣		Press Type		
Low Voltage Protection 低壓截止保護線路		Electronic Protection (approx. 1V / cell)		
Compliance To 達致認可標準		BS 5266-1, BS EN 60598-2-22 and FSD PPA/104A(4th Revision)		
Guarantee Period 保用期	(M)	12 months		

Options: Sealed Ni-MH High Temp. Rechargeable Battery will be available on request.

[:] Clients can choose 30% or 50% lumen output when mains fail.



JOHNSON






JXP10SN3-Elite-W, 1x10W emergency sign plate, white escape route sign with upward arrow on green background.



JXP10SNH3-Elite-T, c/w NI-MH rechargeable battery.



JXP10SNH3-Elite-T



^{** &}quot;JOHNSON" ELITE series are used spring to lock in the box or screws to fix with the box. It depends on the clients needs.